

HYGINOX SH



SANITARY CENTRIFUGAL PUMP

For Cleaning systems (CIP), Bottling, Filtration and auxiliary services for industry.

In stainless steel AISI 316L, IEC standard motors and DIN 24960 mechanical seals.

Flows up to 150 m³/h.

Maximum pressure 100 m.w.c.

Maximum working temperature 120° C

CAPACITY	HEAD	Inlet	Outlet	PUMP SIZE	POWER	SPEED	PRICE
m ³ /h	m.w.c.	DN	DN	SH	KW	RPM	DEM
10	12	40	32	SH-15A	0,55	3000	1443
20	20	50	40	SH-20C	2,2	3000	1883
30	30	65	50	SH-26E	4	3000	2271
40	30	65	50	SH-26F	5,5	3000	2645
5	35	40	40	SH-28C	2,2	3000	2143
10	50	40	40	SH-28E	4	3000	2405
30	35	65	50	SH-35F	5,5	3000	2847
20	60	65	50	SH-35F	7,5	3000	3054
50	40	65	50	SH-35F	9	3000	3231
40	55	65	50	SH-35G	11	3000	3709
60	10	100	65	SH-38E	4	1500	2785
90	2	100	65	SH-38F	5,5	1500	2844
60	40	100	65	SH-38G	11	3000	3976
60	60	100	65	SH-38G	15	3000	4383
80	50	100	65	SH-38G	18,5	3000	4725
100	50	100	65	SH-38H	22	3000	5328
130	40	100	65	SH-38J	30	3000	6743

For specific applications, please, send your inquiries.
We will select for you the most suitable pump.